




MICRO-FLUIDIZATION PRODUCTS FOR INDUSTRY



CIRCULAR SAWING APPLICATIONS

Messy and costly flood coolants are the old way to provide lubrication for circular sawing applications. The uni-MAXLUBRICATION process is the right way!



uni-MAX low maintenance equipment will apply minimal amounts of COOLUBE 2210 high efficiency lubricant to the saw blade/workpiece interface and reduce heat generation while keeping the saw blade cool. This process can be used for sawing any metal, composite, wood or plastic.

System Operation

Using a series of uni-MAX building blocks, UNIST will specify a system to apply "one-shot" (for short cycles) or a continuous spray system to maintain a very thin film of lubricant on your circular saw blade. This system uses compressed air as its power source and positive displacement pumps to deliver metered fluid to the nozzle tip(s) where it is slightly atomized.

UNIST will assist you with nozzle selection, possible magnetic bases, hose length, lockable enclosures, reservoirs and on-off controls. Just FAX us your completed questionnaire from the reverse side

Features and Benefits of Coolubing with uni-MAX equipment.

Coolube 2210 Lubricant

- Minute usage
- Biodegradable
- Non-toxic
- Consumed in operation
- Clean
- No disposal
- No recycling
- No mess
- Limited cleaning

UNIST System

- Steel enclosure
- Intermittent or continuous output
- 10 oz. to 30 gal. reservoirs
- Unlimited nozzles per system
- Easy adjustment
- Viton seals standard

[Data sheet/Fax Application Questionnaire](#)

Consider the Band Sawing applications in your plant and [CLICK HERE](#) to complete the application questionnaire for a specific quotation

UNIST, Inc. - 4134 36th St. SE - Grand Rapids, MI 49512 USA (616) 949-0853 - (800) 253-5462 - Fax (616) 949-9503
<mailto:unimail@unist.com>

Copyright 2001/2004 UNIST INC. Last Revision 09/13/04