



MICRO-FLUIDIZATION PRODUCTS FOR INDUSTRY



DRILLING APPLICATIONS

Messy and costly flood coolants are the old way to provide lubrication for single or multiple drilling applications. The uni-MAX COOLUBING process is the right way!



uni-MAX low maintenance equipment will apply minimal amounts of Coolube 2210 high efficiency lubricant to the drilling tool/work-piece interface and reduce heat generation while keeping the drill cool. COOLUBING can be used for drilling any metal, composite, wood or plastic.

System Operation

Using a series of uni-MAX "building blocks", UNIST will specify a system to apply "one-shot" (for short cycles) or a continuous spray system to maintain a very thin film of lubricant on your drill. This system uses compressed air as its power source and positive displacement pumps to deliver metered fluid to the nozzle tip(s) where it is slightly atomized. UNIST also has equipment to meet all your coolant-fed tooling needs.

UNIST will assist you with nozzle selection, possible magnetic bases, hose length, lockable enclosures, reservoirs and on-off controls. Just FAX us your completed questionnaire from the reverse side.

Features and Benefits of Coolubing with uni-MAX equipment.

Coolube 2210 Lubricant

- Minute usage
- Biodegradable
- Non-toxic
- Consumed in operation
- Clean
- No disposal
- No recycling
- No mess
- Limited cleaning

UNIST System

- Steel enclosure
- Intermittent or continuous output
- 10 oz. to 30 gal. reservoirs
- Unlimited nozzles per system
- Easy adjustment
- Viton seals standard

[Data sheet/Fax Application Questionnaire](#)

Consider the Band Sawing applications in your plant and [CLICK HERE](#) to complete the application questionnaire for a specific quotation

UNIST, Inc. - 4134 36th St. SE - Grand Rapids, MI 49512 USA (616) 949-0853 - (800) 253-5462 - Fax (616) 949-9503
mailto:unist@unist.com

Copyright 2001/2004 UNIST INC. Last Revision 09/13/04