




MICRO-FLUIDIZATION PRODUCTS FOR INDUSTRY



MILLING APPLICATIONS

Messy and costly flood coolants are the old way to provide lubrication for single or multiple milling applications. The uni-MAX COOLUBING process is the right way!



uni-MAX low maintenance equipment will apply minimal amounts of Coolube 2210 efficiency high lubricant to the milling cutter/workpiece interface and reduce heat generation while keeping the milling cutter cool. COOLUBING can be used for milling any metal, composite, wood or plastic.

System Operation

Using a series of uni-MAX "building blocks", UNIST will specify a system to apply small amounts of lubricant to the milling (routing) cutter. This system uses compressed air as its power source and automatically cycled positive displacement pumps will meter fluid to the nozzle tip where it will be slightly atomized.

Features and Benefits of Coolubing with uni-MAX equipment.

Coolube 2210 Lubricant

- Minute usage
- Biodegradable
- Non-toxic
- Consumed in operation
- Clean
- No disposal
- No recycling
- No mess
- Limited cleaning

UNIST System

- Steel enclosure
- Intermittent or continuous output
- 10 oz. to 30 gal. reservoirs
- Unlimited nozzles per system
- Easy adjustment
- Viton seals standard

[Data sheet/Fax Application Questionnaire](#)

Consider the Band Sawing applications in your plant and [CLICK HERE](#) to complete the application questionnaire for a specific quotation

UNIST, Inc. - 4134 36th St. SE - Grand Rapids, MI 49512 USA (616) 949-0853 - (800) 253-5462 - Fax (616) 949-9503
<mailto:unimail@unist.com>

Copyright 2001/2004 UNIST INC. Last Revision 09/13/04