



MICRO-FLUIDIZATION PRODUCTS FOR INDUSTRY



ASSEMBLY APPLICATIONS

Hand, brush and aerosol applications are the old way to provide lubrication for assembly applications. The uni-MAX COO LUBING process is the right way!

uni-MAX low maintenance systems apply minimal amounts of COOLUBE 2210 high efficiency lubricant to the assembly tool/part interface and reduce friction. COOLUBING can be used for many types of assembly operations using metal, composite, rubber or plastic components.

System Operation

Using a series of uni-MAX "building blocks", UNIST will specify a system to allow you to precisely and consistently lubricate the inside and/or outside of any parts being assembled. The system will use compressed air as its power source and will accurately apply the proper amount of lubricant to the required surfaces.

Coolube 2210 Lubricant

- Minute usage
- Biodegradable
- Non-toxic
- Consumed in operation
- Clean
- No disposal
- No recycling
- No mess
- Limited cleaning

UNIST System

- Steel enclosure
- Intermittent or continuous output
- 10 oz. to 30 gal. reservoirs
- Unlimited nozzles per system
- Easy adjustment
- Viton seals standard

Features and Benefits of Coolubing with uni-MAX equipment.

[Data sheet/Fax Application Questionnaire](#)

Consider the Sawing applications in your plant and [CLICK HERE](#) to complete the application questionnaire for a specific quotation

UNIST, Inc. - 4134 36th St. SE - Grand Rapids, MI 49512 USA (616) 949-0853 - (800) 253-5462 - Fax (616) 949-9503
mailto:unistmail@unist.com

Copyright 2001/2004 UNIST INC. Last Revision 09/13/04